



## DIESEL 4000 C

PORTABLE POWER

50Hz range Diesel

### PRODUCT ADVANTAGES


- Entire group guaranteed 3 years
- KOHLER Professional Engine
- Low consumption
- Comfort of prehension thanks to the ergonomic handles
- Compact frame with protection panels against shocks

### Zoom

A both large autonomy and very long life for professional applications.

### Divers

A both large autonomy and very long life for professional applications.



## DIESEL 4000 C

### GENERAL SPECIFICATIONS

Range	Diesel
Frequency (Hz)	50
Max. power (LTP) (kW)	3.40
Max power. (LTP) (kVA)	4.25
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Guaranteed acoustic power Lw(A)	108
Noise level dB(A) - 1m	92
Sound level dB(A) - 7m	78

### ENGINE SPECIFICATIONS

Engine type	KD350
Autonomy (h)	4.80
Consumption (L/h]	0.90
Tank (L)	4.30
Oil Guard	No
Capacity (cm <sup>3</sup> )	349
Oil capacity (L)	1.20

### ALTERNATOR SPECIFICATIONS

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

### PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

### DIMENSIONS AND WEIGHT

Lenght (cm)	81
Width (cm)	55.50
Height (cm)	59
Dry Weight (kgs)	70

### PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56.50
Height (cm)	60
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193

## ACCESSORIES SUPPLIED

User and maintenance manual

## OPTIONS



R01	Differential box R01	This set includes the hour meter and the differential circuit breaker.
R05M	Manual changeover switch	The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.
RKB1	RKB1 trolley kit	Trolley kit for the generating sets of 6kW or below
RPM	Set of male plugs RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V
RPQ	Earth spike RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm <sup>2</sup> cable.
RBAC	Storage box	Removable storage box